

# RM300 HH



## ON/OFF-ROAD DRIVE

The RM300 HH is an on/off-road drive tire designed to handle heavy hauling. The deep traction pattern, tread compounding and high tensile strength four-belt package combine to provide the retreadability, treadwear, and cut and chip resistance that your fleets require.

**M+S Rated**

### STONE PROTECTOR LEDGE

Stone protector ledges on all lugs resist stone penetrations.

### STONE EJECTORS

Stone ejectors in the bottom of the tread grooves protect the casing from stone penetrations.

### CURB BAR WITH SIDEWALL DEPTH INDICATOR

Protects the sidewall from scuffing damage and indicates when a tire should be rotated to preserve the casing for retreading.

### CUT AND CHIP RESISTANT TREAD COMPOUND

The cut and chip resistant tread compounding is specifically designed to perform in mixed service applications.

### DEEP TREAD DEPTH

Rugged 29.5/32" of tread provides excellent traction and durability.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000007287	93734	11R22.5 H/16 146/143K 68 mph 110 km/h	(8.25) 7.5-8.25	120 830	6,610 3,000	6,005 2,725	42.09 1,069	11.20 284	19.57 497	12.5 318	493 306	29.5 23.5	26 660	9.02 229	127 57.7	029142663669
90000007288	93756	11R24.5 H/16 149/146K 68 mph 110 km/h	(8.25) 7.5-8.25	120 830	7,160 3,250	6,610 3,000	44.09 1,120	11.10 282	20.59 523	12.5 318	470 292	29.5 23.5	26 660	9.02 229	135 61.5	029142663676

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit [cooperworld.net](http://cooperworld.net) for up-to-date spec information.