

RM185

SmartWay
Verified



**REGIONAL HAUL
PICK-UP AND DELIVERY
ALL-POSITION
SMARTWAY VERIFIED**

The RM185 is a regional all-position tire that is SmartWay verified for steer axle applications. The solid shoulder tread design and high tensile strength four-belt construction combine to provide the retreadability, treadwear and fuel efficiency to meet your fleet's requirements.

**SMARTWAY VERIFIED
LOW ROLLING RESISTANCE TIRE**

Tire design and rubber compounding provide low tire rolling resistance and contribute to fuel efficiency.

ROBUST ALL-POSITION TREAD PATTERN

18 / 32" tread depth combined with solid shoulder ribs make this tire ideally suited for regional haul and pick-up and delivery service.

MICRO SIPES ON GROOVES EDGES

Provide enhanced traction in wet road conditions and resists "river wear."

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000007235	97853	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.0) 8.25-9.0	110 760	6,175 2,800	5,675 2,575	40.12 1,019	10.90 278	18.74 476	13.2 335	517 321	18.0 460	26 660	8.74 222	108 49.1	029142676614
90000007230	92034	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.5-8.25	105 720	6,175 2,800	5,840 2,650	41.42 1,052	10.80 274	19.29 490	12.5 318	501 311	18.0 460	24 610	8.50 216	111 50.6	029142648932
90000007229	92036	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	120 830	6,610 3,000	6,005 2,725	41.42 1,052	10.80 274	19.29 490	12.5 318	501 311	18.0 460	24 610	8.50 216	113 51.4	029142648949
90000007233	92045	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 8.25-8.25	110 760	6,175 2,800	5,675 2,575	41.50 1,054	10.70 273	19.49 495	12.5 318	500 310	18.0 460	26 660	8.39 213	114 51.7	029142648987
90000007232	92054	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	105 720	6,610 3,000	6,005 2,725	43.46 1,104	11.00 279	20.31 516	12.5 318	477 296	18.0 460	22 559	8.74 222	119 54.2	029142648956
90000007231	92056	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.5-8.25	120 830	7,160 3,250	6,610 3,000	43.46 1,104	11.00 279	20.31 516	12.5 318	477 296	18.0 460	22 559	8.74 222	121 55.1	029142648963

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.