

RM120



LONG HAUL TRAILER AND ALL-POSITION

The RM120 is a long haul trailer tire that has an optimized tread depth and high tensile strength four-belt package combine to provide the retreadability and even treadwear that your fleets require.

MICRO SIPES ON GROOVES EDGES

Provide enhanced traction in wet road conditions and resists "river wear."

STONE EJECTORS

Stone ejectors in the tread grooves protect the casing from stone penetrations.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000007212	98153	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.0) 8.25-9.0	110	6,175	5,675	39.65	11.00	18.54	13.2	523	12.0	26	8.74	100	029142676645
				760	2,800	2,575	1,007	279	471	335	325	9.5	660	222	45.3	
90000007206	92334	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.5-8.25	105	6,175	5,840	41.10	10.90	19.17	12.5	504	12.0	24	8.50	103	029142649113
				720	2,800	2,650	1,044	276	487	318	313	9.5	610	216	46.9	
90000007207	92336	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	120	6,610	6,005	41.10	10.90	19.17	12.5	504	12.0	24	8.50	105	029142649120
				830	3,000	2,725	1,044	276	487	318	313	9.5	610	216	47.8	
90000007211	92345	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 8.25-8.25	110	6,175	5,675	40.94	10.80	19.25	12.5	506	12.0	24	8.62	107	029142649168
				760	2,800	2,575	1,040	275	489	318	315	9.5	610	219	48.4	
90000007210	92354	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	105	6,610	6,005	43.15	10.90	20.16	12.5	480	12.0	24	8.50	110	029142649137
				720	3,000	2,725	1,096	277	512	318	299	9.5	610	216	50.2	
90000007209	92356	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.5-8.25	120	7,160	6,610	43.15	10.90	20.16	12.5	480	12.0	24	8.50	112	029142649144
				830	3,250	3,000	1,096	277	512	318	299	9.5	610	216	51.1	

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.