

RM332 WB



**ON / OFF ROAD
PREMIUM ALL-POSITION
WIDE BASE**

The new, premium RM332 WB is a heavy-duty, wide base tire designed for the steer axle in mixed service applications. The rib-type tread pattern was specially designed to withstand the rigors of on/off-road, heavy haul driving while also providing great tread life and even wear. Through its specially formulated tread compound and heavy-duty four belt construction, this tire will deliver the performance and durability that fleets demand.

23/32" DEEP TREAD DEPTH

23/32" tread depth provides extended tread life in severe, high-scrub applications.

RIB-TYPE TREAD DESIGN FOR STEER AXLES

The rib-type tread pattern promotes great tread life and even wear in mixed service applications.

CUT AND CHIP RESISTANT TREAD COMPOUND

The cut and chip resistant compound was specially formulated to meet the performance requirements in mixed service applications.

FOUR HEAVY-DUTY, FULL-WIDTH STEEL BELT CONSTRUCTION

Four heavy-duty, full-width steel belts promote durability in heavy-haul fleets while also preserving the casing for retread.

STONE PROTECTOR LEDGES

The stone protector ledges in all four circumferential grooves help resist stone penetrations, thereby preserving the casing for retread.

CURB BAR ON SIDEWALLS

The curb bar on both sidewalls protects the tire from curbing damage thus helping to preserve the casing for retread.

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000022869	385/65R22.5 L/20 160K 68 mph 110 km/h	(11.75) 11.75-12.25	130 900	9,920 4,500	n/a n/a	42.32 1,075	15.20 385	19.57 497	n/a n/a	490 304	23.0 18.1	46 1,168	12.24 311	180 81.7	029142818700
90000022900	425/65R22.5 L/20 165K 68 mph 110 km/h	(12.25) 11.75-13.0	120 830	11,400 5,150	n/a n/a	44.53 1,131	16.08 431	20.51 521	n/a n/a	466 289	23.0 18.1	46 1,168	13.50 343	203 92.3	029142818717

Please call Cooper Tire's Consumer Relations Department for a proper fitment recommendation if using this product in a dual application.

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.