

RM254



REGIONAL PICK-UP AND DELIVERY DRIVE

The RM254 is a regional traction tire. Whether on a beverage truck or delivery truck, this tire will provide the traction and treadwear required for frequent stopping and accelerating. The premium tread compound and high tensile strength four-belt package combine to provide the retreadability, treadwear, and traction to meet your fleet's expectations.

M+S Rated

AGGRESSIVE TRACTION TREAD PATTERN

Provides superior performance in all types of conditions.

ROBUST TIE-BARS

Provide support and to resist cracking, tearing and heel-toe wear.

STONE PROTECTOR LEDGE

Stone protector ledges on lugs resist stone penetrations.

CURB BAR WITH SIDEWALL DEPTH INDICATOR

Protects the sidewall from scuffing damage and indicates when a tire should be rotated to preserve the casing for retreading.

CUT AND CHIP RESISTANT TREAD COMPOUND

The cut and chip resistant tread compounding used for the load range H sizes was specifically designed to perform for mixed service applications.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000007271	71053	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.0) 8.25-9.0	110 760	6,175 2,800	5,675 2,575	40.75 1,035	11.10 281	19.02 483	13.2 335	509 316	26.0 20.7	28 711	9.00 229	117 53.3	029142731993
90000007269	71034	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.5-8.25	105 720	6,175 2,800	5,840 2,650	41.93 1,065	11.20 284	19.49 495	12.5 318	494 307	26.0 20.7	26 660	8.60 218	120 54.5	029142731955
90000007270	71036	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	120 830	6,610 3,000	6,005 2,725	41.93 1,065	11.20 285	19.53 496	12.5 318	494 307	26.0 20.7	26 660	8.60 218	122 55.3	029142731962
90000007274	71045	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 8.25-8.25	110 760	6,175 2,800	5,675 2,575	41.93 1,065	10.80 274	19.65 499	12.5 318	494 307	26.0 20.7	28 711	9.00 229	122 55.6	029142732006
90000007272	71054	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	105 720	6,610 3,000	6,005 2,725	43.94 1,116	11.20 285	20.51 521	12.5 318	472 293	26.0 20.7	26 660	8.60 218	128 58.2	029142731979
90000007273	71056	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.5-8.25	120 830	7,160 3,250	6,610 3,000	43.94 1,116	11.20 285	20.51 521	12.5 318	472 293	26.0 20.7	26 660	8.60 218	130 59.1	029142731986

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.