

RM234

**SmartWay
Verified**



**REGIONAL HAUL
PREMIUM ALL-POSITION
SMARTWAY VERIFIED**

The RM234 is now SmartWay verified. This is still a premium regional all position tire for high scrub applications with deep tread grooves and a premium tread compound providing excellent treadwear and cut and chip resistance.

 ENERGY MAX FUEL EFFICIENT COMPOUND

The tire's tread design and rubber compounding provides low tire rolling resistance and contributes to fuel efficiency, earning SmartWay verification.

DEEP TREAD DEPTH

22.5/32" tread depth provides extended mileage in high scrub applications.

PREMIUM HIGH SCRUB TREAD COMPOUND

Premium tread compound developed to increase treadwear and provide solid protection against cutting and chipping.

STONE EJECTORS

Stone ejectors in the tread grooves protect the casing from stone penetrations.

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000026379	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.0) 8.25-9.0	110 760	6,175 2,800	5,675 2,575	40.35 1,025	11.10 283	18.82 478	13.2 335	514 319	22.5 18.0	30 762	8.87 225	115 52.1	029142849278
90000029726	295/75R22.5 H/16 149/146L 75 mph 120 km/h	(9.0) 8.25-9.0	125 850	7,160 3,250	6,610 3,000	40.35 1,025	11.10 283	18.82 478	13.2 335	514 319	22.5 18.0	30 762	8.87 225	113 51.5	029142893233
90000026378	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.5-8.25	105 720	6,175 2,800	5,840 2,650	41.69 1,059	11.10 283	19.41 493	12.5 318	497 309	22.5 18.0	26 660	8.87 225	119 54.0	029142849261
90000026377	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	120 830	6,610 3,000	6,005 2,725	41.69 1,059	11.10 283	19.41 493	12.5 318	497 309	22.5 18.0	26 660	8.87 225	121 55.2	029142849254
90000026502	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 8.25-8.25	110 760	6,175 2,800	5,675 2,575	41.69 1,059	10.90 276	19.57 497	12.5 318	497 309	22.5 18.0	30 762	8.87 225	120 54.6	029142850007
90000026501	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	105 720	6,610 3,000	6,005 2,725	43.66 1,109	11.10 282	20.39 518	12.5 318	475 295	22.5 18.0	26 660	8.87 225	129 58.6	029142849292
90000026500	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.5-8.25	120 830	7,160 3,250	6,610 3,000	43.66 1,109	11.10 282	20.39 518	12.5 318	475 295	22.5 18.0	26 660	8.87 225	129 58.6	029142849285

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.