

RM185HH



REGIONAL AND HIGHWAY HAULER ALL-POSITION

The RM185HH is a regional all-position tire designed to handle the heavy hauling. The 5-rib tread design and high tensile strength four-belt package combine to provide the retreadability and treadwear that your fleets require.

5-RIB TREAD DESIGN

Chevron shaped ribs provide good mix of wear and traction for the premium highway hauler.

RADIAL SIPING

The radial siping enhances wet traction and braking.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REV's miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000007234	91838	315/80R22.5 J/18 154/151L 75 mph 120 km/h	(9.0) 9.0-9.75	120 830	8,270 3,750	7,610 3,450	42.24 1,073	12.40 314	19.65 499	13.8 351	491 305	18.0 14.5	26 660	9.49 241	128 58.3	029142685043

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.