

RM230 HH



ON/OFF-ROAD ALL-POSITION

The RM230HH is an on/off-road all-position tire designed to handle heavy hauling. The robust tread pattern, tread compounding and high tensile strength four-belt package combine to provide the retreadability, treadwear, and cut and chip resistance that your fleets require.

CUT AND CHIP RESISTANT TREAD COMPOUND

The cut and chip resistant tread compounding is specifically designed to perform in mixed service applications.

STONE PROTECTOR LEDGE

Stone protector ledges on all grooves resist stone penetrations.

CURB BAR WITH SIDEWALL DEPTH INDICATOR

Protects the sidewall from scuffing damage and indicates when a tire should be rotated to preserve the casing for retreading.

DEEP TREAD DEPTH

22.5/32" tread depth provides extended tread life in on/off-road applications.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcng. inch mm	REV's miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000024676	n/a	275/70R22.5 J/18 148/145K 68 mph	(8.25) 7.5-8.25	130	6,940	6,395	37.87	11.10	17.60	11.9	547	22.0	26	8.64	115	029142837602
		110 km/h		900	3,150	2,900	962	281	447	303	340	17.5	660	220	52.3	
90000007239	93336	11R22.5 H/16 146/143K 68 mph	(8.25) 7.5-8.25	120	6,610	6,005	41.65	11.10	19.41	12.5	498	22.5	26	9.02	123	029142663843
		110 km/h		830	3,000	2,725	1,058	283	493	318	309	18.0	660	229	56.1	
90000007238	93322	12R22.5 H/16 150/147K 68 mph	(9.0) 8.25-9.0	120	7,390	6,780	42.91	12.00	19.92	13.5	483	22.5	26	9.61	142	029142692850
		110 km/h		830	3,350	3,075	1,090	304	506	343	300	18.0	660	244	64.5	
90000007243	93356	11R24.5 H/16 149/146K 68 mph	(8.25) 7.5-8.25	120	7,160	6,610	43.66	11.10	20.39	12.5	475	22.5	26	9.02	132	029142663850
		110 km/h		830	3,250	3,000	1,109	281	518	318	295	18.0	660	229	59.9	
90000007242	93324	12R24.5 H/16 152/149K 68 mph	(9.0) 8.25-9.0	120	7,830	7,160	45.00	12.10	20.94	13.5	461	22.5	26	9.61	152	029142692867
		110 km/h		830	3,550	3,250	1,143	307	532	343	286	18.0	660	244	69.2	

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.