

RM170



PICK-UP AND DELIVERY ALL-POSITION

The RM170 is a pick-up and delivery all-position tire and with the addition of the 17.5" sizes it is also ideal for low-platform trailers. The solid shoulder tread design and high tensile strength belt construction combine to provide the retreadability and treadwear that your local haulers require.

WIDE TREAD AND OPTIMIZED FOOTPRINT

Delivers long, even treadwear.

V-SHAPED TREAD GROOVES

Groove shape works to reduce stone retention.

STONE EJECTORS

Stone ejectors in the tread grooves protect the casing from stone penetrations.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000007215	95804	215/75R17.5 H/16 135/133L 75 mph	(6.0) 6.0-6.75	125	4,805	4,540	30.51	8.40	14.29	9.4	680	15.0	18	7.13	60	029142748656
		120 km/h		850	2,180	2,060	775	214	363	239	422	12.1	457	181	27.1	
90000007216	95805	235/75R17.5 J/18 143/141J 62 mph	(6.75) 6.75-7.5	125	6,005	5,675	31.50	9.40	14.69	10.3	658	15.0	24	7.52	68	029142748663
		100 km/h		860	2,725	2,575	800	238	373	262	409	12.1	610	191	30.8	
90000007217	n/a	225/70R19.5 F/12 125/123L 75 mph	(6.75) 6.0-6.75	95	3,640	3,415	32.09	9.00	14.96	10.0	646	15.0	28	7.60	65	029142678243
		120 km/h		660	1,650	1,550	815	228	380	254	402	11.9	711	193	29.6	
90000007218	95803	225/70R19.5 G/14 128/126L 75 mph	(6.75) 6.0-6.75	110	3,970	3,750	32.09	9.00	14.96	10.0	646	15.0	28	7.60	65	029142678250
		120 km/h		760	1,800	1,700	815	228	380	254	402	11.9	711	193	29.6	
90000007220	95801	245/70R19.5 G/14 133/131L 75 mph	(7.5) 6.75-7.5	110	4,540	4,300	33.11	9.90	15.35	11.0	626	16.0	26	8.39	76	029142678267
		120 km/h		760	2,060	1,950	841	252	390	279	389	12.7	660	213	34.6	
90000007219	95806	245/70R19.5 H/16 136/134M 81 mph	(7.5) 6.75-7.5	120	4,940	4,675	33.11	9.90	15.35	11.0	626	16.0	26	8.39	76	029142750468
		130 km/h		825	2,240	2,120	841	252	390	279	389	12.7	660	213	34.6	
90000007221	95819	265/70R19.5 G/14 137/134L 75 mph	(7.5) 7.5-8.25	110	5,070	4,675	34.33	10.40	15.87	11.6	604	17.5	30	8.62	85	029142721659
		120 km/h		760	2,300	2,120	872	264	403	295	375	13.8	762	219	38.5	
90000027938	n/a	285/70R19.5 H/16 146/144L 75 mph	(8.25) 7.5-9.0	125	6,610	6,170	35.2	11.1	15.87	12.5	589	17.5	30	9.02	86.0	029142872412
		120 km/h		850	3,000	2,800	894	283	403	318	366	13.8	762	229	39.0	
90000007222	95810	10R22.5 G/14 141/139L 75 mph	(7.5) 6.75-8.25	115	5,675	5,355	40.31	10.20	18.82	11.4	514	18.0	24	7.87	101	029142721666
		120 km/h		790	2,575	2,430	1,024	258	478	290	320	14.5	610	200	46.1	

This new size is now available.

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.