

RM272



ALL POSITION SPREAD AXLE TRAILER

The RM272 is an all-position/trailer tire featuring a premium, high-scrub tread compound that provides improved treadwear and solid, long-lasting protection against cutting and chipping in spread axle trailer applications. It is also well suited for straight trucks and recreational vehicles where stopping and starting occur frequently. The stone ejector ribs in the grooves help preserve the casing for retreading and the rounded shoulder design help minimize the effect of high lateral forces on the tire.

PREMIUM HIGH-SCRUB TREAD COMPOUND

The premium tread compound was developed to provide improved treadwear and solid, long-lasting protection against cutting and chipping.

ROUNDED SHOULDER PROFILE

The rounded shoulder design minimizes the effect of high lateral forces in spread axle applications.

STONE EJECTOR RIBS IN TREAD GROOVES

The stone ejector ribs in the center grooves help prevent stone retention and drilling thus preserving the casing for retreading.

MULTI-PURPOSE SIZE DESIGN

The 255/70R22.5 is designed with 16/32 tread depth and is suitable for use on spread-axle trailers, straight trucks and recreational vehicles.

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spc. inch mm	REV's miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000026979	245/70R17.5 J/18 143/141K 68 mph	(7.5) 6.75-7.5	125	6,005	5,675	31.22	9.40	14.41	11.0	664	14.5	22	8.50	69	029142850878
	110 km/h		875	2,725	2,575	793	240	366	279	413	11.5	559	216	31.3	
90000022852	255/70R22.5 H/16 140/137L 75 mph	(7.5) 7.5-8.25	120	5,510	5,070	36.61	10.00	17.24	11.3	566	16.0	28	8.25	92	029142817239
	120 km/h		830	2,500	2,300	930	253	438	287	352	12.5	711	210	41.9	
90000022853	275/70R22.5 J/18 148/145L 75 mph	(8.25) 7.5-8.25	130	6,940	6,395	38.11	10.90	17.68	13.2	544	18.0	28	9.02	108	029142817246
	120 km/h		900	3,150	2,900	968	277	449	335	338	14.5	711	229	49.2	
90000027584	11R22.5 G/14 144/142L 75 mph	(8.25) 7.5-8.25	105	6,175	5,840	43.62	10.90	19.33	12.5	475	16.0	24	8.50	131	029142870715
	120 km/h		720	2,800	2,650	1108	278	491	318	295	12.7	610	216	59.7	
90000033629	11R22.5 H/16 146/143L 75 mph	(8.25) 7.5-8.25	120	6,610	6,005	41.22	11.2	19.21	12.5	503	16.0			113	029142917793
	120 km/h		830	3,000	2,725	1047	284	488	318	313	12.7			51.2	
90000027585	295/75R22.5 G/14 144/141L 75 mph	(9.0) 8.25-9.0	110	6,175	5,675	41.61	10.80	18.58	13.2	498	16.0	28	8.50	123	029142870722
	120 km/h		760	2,800	2,575	1057	275	472	335	310	12.7	711	216	55.9	
90000033791	295/75R22.5 H 149/146L 75 mph	(9.0) 8.25-9.0	125	7,160	6,610	39.88	11.1	20.16	13.2	520	16.0			108	029142917915
	120 km/h		850	3,250	3,000	1013	282	512	335	323	12.7			49.1	
90000033790	11R24.5 H 149/146L 75 mph	(8.25) 7.5-8.25	120	7,160	6,610	43.11	11.2	18.62	12.5	481	16.0			122	029142917908
	120 km/h		830	3,250	3,000	1095	284	473	318	299	12.7			55.4	

New sizes - availability to be announced.

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.