


# RM830



## REGIONAL AND HIGHWAY HAULER ALL-POSITION

The RM830  is a regional all-position tire that is SmartWay verified. The optimized footprint coupled with the five-rib tread design help to deliver long, even wear, while the high tensile strength four-belt package helps to deliver the durability and retreadability fleets require.

### ENERGY MAX FUEL EFFICIENT COMPOUND

The tire's tread design and rubber compounding provides low tire rolling resistance and contributes to fuel efficiency, earning SmartWay verification.

### 5-RIB TREAD DESIGN

Chevron-shaped ribs provide a good mix of even wear and traction.

### RADIAL SIPING

Radial siping enhances wet traction and braking.

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000036217	315/80R22.5 L/20 157/154L 75 mph 120 km/h	(9.0) 9.0-9.75	130 900	9,090 4,125	8,270 3,750	42.24 1,073	12.40 314	19.65 499	13.8 351	491 305	18.0 14.5	26 660	9.49 241	128 58.3	029142936077

The RM830  will be introduced and replaces the RM185HH April 2019.

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.