

RM253



ASYMMETRIC
DRAFT GROOVE WALL



REGIONAL PICK-UP AND DELIVERY DRIVE

The RM253 features sipe siping on the lugs to maximize traction in all types of weather conditions. The aggressive geometric groove base is designed to prevent stone retention and promote self cleaning ability. An all-purpose tread and base compound is specifically formulated for regional pick-up and delivery applications to enhance overall performance.

M+S Rated

MODERN TRACTION TREAD PATTERN

Computer designed tread pattern for an attractive modern appearance providing excellent all-season tire performance (M+S rating). The RM253 complements the RM170 in the steer position.

STONE PROTECTOR LEDGE

Stone protector ledges on lugs resist stone penetrations.

ASYMMETRIC DRAFT GROOVE WALLS

Promotes self-cleaning and to prevent stone retention.

CURB BAR WITH SIDEWALL DEPTH INDICATOR

Protects the sidewall from scuffing damage and indicates when a tire should be rotated to preserve the casing for retreading.

ROBUST CENTER RIB

Engineered to optimize handling response.

APPLICATION-SPECIFIC TREAD COMPOUND

Optimizes treadwear, handling and traction performance for pickup and delivery application.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REV's miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000007265	n/a	225/70R19.5 F/12 125/123L 75 mph 120 km/h	(6.75) 6.0-6.75	95 660	3,640 1,650	3,415 1,550	32.24 819	8.90 225	15.00 381	10.0 254	643 400	18.5 457	18 184	7.24 184	66 29.9	029142721857
90000007266	71826	225/70R19.5 G/14 128/126L 75 mph 120 km/h	(6.75) 6.0-6.75	110 760	3,970 1,800	3,750 1,700	32.24 819	8.90 225	15.00 381	10.0 254	643 400	18.5 457	18 184	7.24 184	66 29.9	029142721864
90000007267	71845	245/70R19.5 G/14 133/131L 75 mph 120 km/h	(7.5) 6.75-7.5	110 760	4,540 2,060	4,300 1,950	33.27 845	9.80 250	15.43 392	11.0 279	623 387	18.5 457	22 559	7.99 203	75 34.2	029142721871
90000007268	71846	245/70R19.5 H/16 136/134M 81 mph 130 km/h	(7.5) 6.75-7.5	120 825	4,940 2,240	4,675 2,120	33.27 845	9.80 250	15.43 392	11.0 279	623 387	18.5 457	22 559	7.99 203	75 34.2	029142750475

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.