

# RM257™



## REGIONAL PICK-UP AND DELIVERY DRIVE

The RM257™ is Roadmaster's open shoulder pick-up and delivery drive tire designed to perform in all weather conditions. 3D siping, shoulder pockets, and chevron grooves all combine to provide this tire with Three-Peak Mountain Snowflake certification for operation in severe weather. The tightly packed center tread blocks and high tensile strength belt construction provide long even wear and the retreadability required by local P&D haulers.



**M+S Rated**

### N (87MPH) SPEED RATING

225/70R19.5 and 245/70R19.5 LR G sizes offer N speed rating.

### CURB BAR

Protects the sidewall from scuffing damage.

### 3D SIPING

3D corrugations on the sipes help to lock the tread blocks together to maintain stability for traction.

### STONE EJECTORS

Stone ejectors in the tread grooves protect the casing from stone penetrations.

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000036421	225/70R19.5 F/12 125/123N 87 mph 140 km/h	(6.75) 6.00-6.00	95 660	3,640 1,650	3,415 1,550	32.24 819	9.06 230	15.00 381	10.0 254	643 400	18.0 457	18 184	7.2 184	65 29.3	029142937913
90000036422	225/70R19.5 G/14 128/126N 87 mph 140 km/h	(6.75) 6.00-6.00	110 760	3,970 1,800	3,750 1,700	32.24 819	9.06 230	15.00 381	10.0 254	643 400	18.0 457	18 184	7.2 184	65 29.3	029142937920
90000036423	245/70R19.5 G/14 133/131N 87 mph 140 km/h	(7.50) 6.75-7.50	110 760	4,540 2,060	4,300 1,950	33.27 845	9.80 250	15.43 392	11.0 279	623 387	19.0 483	22 559	8.0 203	72 32.7	029142937937
90000036424	245/70R19.5 H/16 136/134M 81 mph 130 km/h	(7.50) 6.75-7.50	120 825	4,940 2,240	4,675 2,120	33.27 845	9.80 250	15.43 392	10.6 270	623 387	19.0 483	22 559	8.0 203	72 32.7	029142937944

**This new line will replace the RM253 starting in July 2020.**

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit [cooperworld.net](http://cooperworld.net) for up-to-date spec information.