

# RM275



## LONG HAUL / HIGHWAY AND REGIONAL DRIVE

The RM275 is a long haul drive tire. The solid shoulder traction design and high tensile strength four-belt package combine to provide the retreadability, treadwear and traction to meet your fleet's requirements.

**M+S Rated**

### SOLID SHOULDER DRIVE TIRE

Solid shoulder ribs provide even wear in long haul application, while the lugs provide traction in wet and snow.

### STONE EJECTORS

Stone ejectors in the tread grooves protect the casing from stone penetrations.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000007286	97953	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.0) 8.25-9.0	110 760	6,175 2,800	5,675 2,575	40.59 1,031	11.00 279	18.94 481	13.2 335	511 317	26.5 21.2	26 660	8.74 222	115 52.2	029142676621
90000007281	92134	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.5-8.25	105 720	6,175 2,800	5,840 2,650	42.09 1,069	10.90 276	19.57 497	12.5 318	493 306	26.5 21.2	22 559	8.86 225	122 55.6	029142648994
90000007282	92136	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	120 830	6,610 3,000	6,005 2,725	42.09 1,069	10.90 276	19.57 497	12.5 318	493 306	26.5 21.2	22 559	8.86 225	124 56.4	029142649007
90000007285	92145	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 8.25-8.25	110 760	6,175 2,800	5,675 2,575	41.85 1,063	10.70 272	19.61 498	12.5 318	495 308	26.5 21.2	22 559	8.86 225	118 53.7	029142649045
90000007284	92154	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.5-8.25	105 720	6,610 3,000	6,005 2,725	44.06 1,119	10.70 272	20.55 522	12.5 318	471 292	26.5 21.2	24 610	8.62 219	130 59.3	029142649014
90000007283	92156	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.5-8.25	120 830	7,160 3,250	6,610 3,000	44.06 1,119	10.70 272	20.55 522	12.5 318	471 292	26.5 21.2	24 610	8.62 219	132 60.2	029142649021

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit [cooperworld.net](http://cooperworld.net) for up-to-date spec information.